

# 风冷式冷冻干燥机规格

## Specifications for Air-cooled Refrigerant Drier

干燥机型号 Model of drier	适用空压机 (kW) Adapted compressor (kW)	处理风量 Airflow capacity	耗电功率 (W) Apparent power (W)	空气出入口管径 (英寸) Diameter of air inlet and outlet	使用条件 A. 进气温度 ≤ 35°C B. 相对湿度 ≤ 85% C. 空气压力 ≤ 15 kPa a.c. D. 进气压力 6-10bar	冷冻容量 Refrigerant capacity	制冷剂类型 Refrigerant type	冷凝压力 (MPa) Refrigerant condensing pressure (MPa)	电源 Power supply	重量 (kg) Weight (kg)
 KCS-5AA	3.7	0.6	280	1/2"	●	2-10°C	R-22(R-407)	1/4	AC 1Φ 220V 50Hz/60Hz	55
 KCS-7.5AA	5.5	1.0	280	3/4"	●	2-10°C	R-22(R-407)	1/3	AC 1Φ 220V 50Hz/60Hz	63
 KCS-10AA	7.5	1.5	380	1"	●	2-10°C	R-22(R-407)	1/3	AC 1Φ 220V 50Hz/60Hz	83
 KCS-15AA	11	2.0	505	1 1/4"	●	2-10°C	R-22(R-407)	1/2	AC 1Φ 220V 50Hz/60Hz	85
 KCS-20AA	15	3	505	1 1/2"	●	2-10°C	R-22(R-407)	1/2	AC 1Φ 220V 50Hz/60Hz	87
KCS-30AA	22	4	1260	1 1/2"	●	2-10°C	R-22(R-407)	1 1/3	AC 1Φ 220V 50Hz/60Hz	110
KCS-50AA	37	7.5	1360	2"	●	2-10°C	R-22(R-407)	1 1/2	AC 1Φ 220V 50Hz/60Hz	123
KCS-75AA	56	10.5	2370	2 1/2"	●	2-10°C	R-22(R-407)	2 1/2	AC 3Φ 380V/50Hz 440V/60Hz	199
KCS-100AA	75	15	2770	3"	●	2-10°C	R-22(R-407)	3	AC 3Φ 380V/50Hz 440V/60Hz	238
KCS-150AA	110	22	4270	F3"	●	2-10°C	R-22(R-407)	5	AC 3Φ 380V/50Hz 440V/60Hz	248
KCS-200AA	150	28	4550	F4"	●	2-10°C	R-22(R-407)	5	AC 3Φ 380V/50Hz 440V/60Hz	278

所有技术规格如有变更，恕不另行通知。  
Any change to all technical specifications will not be otherwise notified.